

ACCESSORIES FOR MANOMETERS

TUBES



Ref. TC 5 X 8

Clear tube Ø 5 x 8, for permanent installation (m/l or 25 m).

Ref. TS 4 X 7



Silicone tube Ø 4 x 7 in black or white, for test instruments (m/l).

MANOMETER LIQUIDS



Ref. AWS 10

Density = 0,87. Bottles of : 20 ml, 30 ml, 125 ml, 250 ml, 500 ml, 1000 ml.

Ref. VOLT 1S

Density = 1,86. Bottles of : 10 ml, 20 ml, 30 ml, 125 ml.

Ref. HG

Density = 13,545. Bottles of : 10 ml, 20 ml, 30 ml, 125 ml.

Ref. VF1

Density = 1. Bottles of : 20 ml, 30 ml, 125 ml, 250 ml, 500 ml, 1000 ml.

Ref. TETRA BROMURE

Density = 2,96. Bottles of : 20 ml, 30 ml, 125 ml.

PRESSURE CONNECTIONS :



Ref. KR 483

Connection kit with 2 quick connections n° 483 and 2 m of clear tube.



Ref. DP 339

Connection for double-shell wall maximum thickness : 80 mm. Drilling diameter : 6 mm.



Ref. DP 447

Connection for double-shell wall, maximum thickness : 30 mm. Drilling diameter : 6 mm.



Ref. 483

Quick-connection for wall without rear access. Drilling diameter : 10 mm.



Ref. 482

Simple connection with rear nut, M5 threading, length 15 mm. Drilling diameter : 5 mm.



Ref. PC 482

Through-connection for partitions standard lengths 35 to 190 mm. Other lengths on request. Drilling diameter : 11 mm.


MANOMETERS CONNECTIONS :



Ref. 487
Simple connection in chromed brass for all type of manometers using AWS 10 and VOLT 1S. Thread : 1/8 gas.




Ref. 505
Valve connection in chromed brass for portable MT, KM, TJ and LU manometer using VOLT 1S liquid. Thread : 1/8 gas.



Ref. 466
Simple connection in nylon for GF manometers, using VF1 and HG liquid. Thread : 7 x 100.




Ref. 509
Chromed brass safety connection, eliminating overspill on manometer using AWS 10 and VOLT 1S. Thread : 1/8 gas.




Ref. 484
Simple connection in nylon for TJ and LU mercury manometers. Thread : 1/8 gas.



Ref. 555 F/F
Female / female, 1/8 gas ball valve, for manometer isolation.



Ref. 555 M/F
Male / female, 1/8 gas ball valve, for manometer isolation.



Ref. 666
Male / female, 1/8 connection, air vent valve with a slide block to set the zero point without disconnecting the tubes.

JUNCTIONS



Ref. J.D.C
Straight connection for Ø 5 x 8 tube.



Ref. J.T.C
T-connection for Ø 5 x 8 tube.



Ref. J.Y.C
Y-connection for Ø 5 x 8 tube.

ACCESSORIES

Ref. 494
Pressure tube, length 1 m for MT and KM manometers. With moulded ends.

Ref. FM-KS.10
Set of 2 magnetic fixings.

Ref. 648-FM
Safety reservoir, with magnetic fixings for mercury manometers.

Ref. GPN 900
Plug -8,5 A for all Ø 6,2 mm connections. 10 units bag.

Ref. 648-PF
Safety reservoir, permanent fixing for mercury manometers.

Ref. ALTU.
Altunet cleaning product, 500 ml bottle..

www.kimo.fr

Distributed by :



EXPORT DEPARTMENT
Tel : + 33. 1. 60. 06. 69. 25 - Fax : + 33. 1. 60. 06. 69. 29
e-mail : export@kimo.fr