

1150°C




**Thermocouple K sensor
for high temperature
with ceramic protection .**

TBAL K / TBALD K

- Thermocouple K.
- Working temperature : up to +1150°C.
- Mounting with ceramic sheath.


Part numbers



Example : TBAL-K-100-500-15


Model : Thermocouple type K, sheath of 15 mm Ø with a coupling of 100 mm length and a ceramic of 400 mm length. LU is 500 mm.

Dimensions



Accessories (See related FT)

- Extension cable
- Compensating cable
- Standard or miniature connector
- Cable seal for plug and socket connector
- Miniature or standard fixed connector
- Miniature or standard connectors panel
- Extension lead
- Converters



Technical features

Maximum operating temperature ..+1150°C

Accuracy*.....± 0,0075 t t l

Sheath.....Coupling 21,3 mm Ø
(Customized length)

Watertight refractory ceramic sheath
(CRE 610)
Standard 15 mm Ø (Other on request)
(Customized length)

Mounting.....Wires in ceramic pearls
couple of wires Ø 2.9 mm (singlepair)
or Ø 2.3 mm (multipair)
(Other on request)

Connection head.....Aluminium alloy (120°C max)
steel cable gland : M20 x 150
IP54 protection

Storage temperature.....from -20°C to +80°C

Tolerances* of the probe

As per IEC 584-3 norm

TC	Measuring range Class 1	Tolerance
K	from -40°C to +1000°C	from -40°C to +375°C ± 1.5°C from 375°C to 1000°C ± 0.004 x T° abs

* Performed in laboratory conditions, the above accuracies mentioned in this document will be guaranteed, provided that you use the calibration compensation data or identical calibration conditions.

Most common thermocouple types

Thermocouple type	+ conductor	- conductor	Color of compensating cable
K	Chromel	Alumel	Ext. color + = green, - = white

Distributed by :

www.kimo.fr



EXPORT DEPARTMENT
Tel : + 33. 1. 60. 06. 69. 25 - Fax : + 33. 1. 60. 06. 69. 29
e-mail : export@kimo.fr